▲Hanna Ave 4000 OFFICE OF THE MARION COUNTY SURVEYOR SECTION RECORD CORNER SECTION _____35__TOWNSHIP __ DATE: ___7-22-05 15___ RANGE __2 PARTY CHIEF: Wilcoxen CREV: TYPE OF MARKER: Brass plug in poured concrete METHOD OF ESTABLISHMENT: County: 3-18-02 Set by GPS & others IN. S.P.C. E ZONE NAD NAME: 15023501 N: 495033.8200(m) E: 46693.4240(m) SEpler. 55.00 S ounty (70) New 1-70 to SixPoints exit

Original post set 1820 by Laughlin with witness: 5" white oak N 81 W 20 links, 14" beech S 55 E 26 links per Marion County Atlas pg. 2. Hosbrook 4-4-1851 called no stone but placed the corner by a little ash tree said to be where the original stake stood from the recollection of an "old" quaker man per Decatur Township Legal Survey Book pg. 2. Monroe 5-26-61 called pipe over stone. Howe 12-27-74 called PK nail. Greene 7-2-86 called PK nail. Wilcoxen 12-17-95 called brass plug 2" down. Excavated by **Kiste**8-26-97 and brass plug found 3" down in concrete. Harrison set. Re-tied 3-18-02 by Kiste. Re-tied 7-22-05 by Wilcoxen.

REF.	DISTANCE	DESCRIPTION
1	2.50	N face of survey sign post
		Light and the state of the stat